

5-1/8" HD Slick-Catch Overshot

Description

The HD Slick-Catch Overshot engages the fish with a 360 degree collet/grapple. The grapple has special treated grip area to withstand heavy jarring.

To release from the fish, jar down and shear pins inserted to match the down forces.

The overshot has been designed to withstand heavy duty jarring/impact force, and all components has been exposed to comprehensive testing to provide a safe controlled release of down hole equipment.

The overshot can be supplied with different grapples making it possible to engage fishes from 2" to 4"

The overshot will preferably be run with a Bell Guide to help guide the fish into the overshot. This will give the tool a bigger OD depending on the Bell Guide applied.

Specifications

Tool OD	5,125 in / 82,55 mm
Tool length	34,3 in / 871 mm
Tool Weight	88 lbs. / 40 kg
Fishing neck	2,312 in / 58,74 mm
Top connection	2-7/8" HD EasyConnect
Metal quality	Standard Service
Yield	191 Klbs / 86600 kg
Ultimate Tensile strength	220 Klbs / 99790 kg
Reach	175 mm- 1370mm(Extender)
Grapple reach	2,00" – 4,00"
Available Bell Guides	5-3/4" and 6-1/8"
IFS Part Nr	1574228

Archer

Archer

Finnestadveien 24
P.O. Box 338
N-4002 Stavanger
Norway
Tel: +4751308000
archerwell.com